



Crafted.  
Honed.  
Perfected.

Introducing the new 700 Series Signature. The 700 Series Signature combines state-of-the-art engineering with the highest possible standards of design, finish and quality. Every speaker is crafted with care, honed by experience and perfected with passion.

## Crafted

Exquisite Datuk Gloss finish for loudspeakers that look as beautiful as they sound. Each pair of speakers is unique, with no two models sharing the same grain pattern.



## Honed

Expertly tuned for exceptional detail and clarity, enabled by upgraded crossover designs and components.



## Perfected

Signature is the culmination of decades of loudspeaker design. It embodies everything we know – and here, it's applied to 700 Series for the first time.





## 702 Signature

<b>Technical features</b>	Decoupled Carbon Dome™ tweeter Solid Body Tweeter on top Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™
<b>Description</b>	3-way vented-box system
<b>Drive Units</b>	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø150mm (6 in) Continuum cone FST midrange 3x ø165mm (6.5 in) Aerofoil Profile bass
<b>Frequency range (-6dB)</b>	-6dB at 28Hz and 33kHz
<b>Frequency response</b>	45Hz - 28kHz ±3dB
<b>Sensitivity</b>	90dB spl (2.83V <sub>RMS</sub> , 1m)
<b>Harmonic distortion</b>	2nd and 3rd harmonics (90dB, 1m) <1% 86Hz - 28kHz <0.5% 110Hz - 20kHz
<b>Nominal impedance</b>	8Ω (minimum 3.1Ω)
<b>Recommended amplifier power</b>	30W - 300W into 8Ω on unclipped programme
<b>Dimensions Height:</b>	994mm (39 in) cabinet only 1087mm (42.8 in) including tweeter and plinth 200mm (7.9 in) cabinet only
<b>Width:</b>	366mm (14.4 in) including plinth 337mm (13.3 in) cabinet only 364mm (14.3 in) including grille and terminals
<b>Depth:</b>	414mm (16.3 in) including plinth
<b>Weight</b>	29.5kg (65 lb)
<b>Finishes</b>	<b>Cabinet:</b> Datuk Gloss <b>Grille:</b> Black



## 705 Signature

<b>Technical features</b>	Decoupled Carbon Dome tweeter Solid Body Tweeter on top Continuum cone bass / midrange Flowport
<b>Description</b>	2-way vented-box system
<b>Drive Units</b>	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø165mm (6.5 in) Continuum cone bass / midrange
<b>Frequency range (-6dB)</b>	-6dB at 45Hz and 33kHz
<b>Frequency response</b>	50Hz - 28kHz ±3dB
<b>Sensitivity</b>	88dB spl (2.83V <sub>RMS</sub> , 1m)
<b>Harmonic distortion</b>	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 150Hz - 20kHz
<b>Nominal impedance</b>	8Ω (minimum 3.7Ω)
<b>Recommended amplifier power</b>	30W - 120W into 8Ω on unclipped programme
<b>Dimensions Height:</b>	340mm (13.4 in) cabinet only 407mm (16 in) including tweeter 200mm (7.8 in)
<b>Width:</b>	285mm (11.2 in) cabinet only
<b>Depth:</b>	301mm (11.9 in) including grille and terminals
<b>Weight</b>	9.3kg (20.5 lb)
<b>Finishes</b>	<b>Cabinet:</b> Datuk Gloss <b>Grille:</b> Black

